4. Size Considerations

4.1 Single Shade (For Sheer/Light Filtering/Room Darkening/Whispers Fabric)

Lift Systems	Width		Height		Max. Area
	Min	Max	Min	Max	
SmartRise™ Cordless	280mm[5]	2500mm	250mm	2400mm[4]	5.5 SQM
Cordless TDBU	380mm[6]				5.5 SQM
Cordless Day & Night					
SmartFit™ Bottom Up	220mm	1820mm	150mm	2438mm	4 SQM
SmartFit™	220mm	1800mm[1]	150mm	2200mm	4 SQM[2]
SmartFit™ for Sloped Windows	220mm	1500mm	150mm	3000mm	4.5 SQM
SmartFit™ Day & Night (25mm S)	220mm	1270mm	310mm	2200mm	2.6 SQM[2]
SmartFit™ Day & Night (45mm S, 45mm D, 62mm S, and 62mm Double)	220mm	1800mm	310mm	2200mm	4 SQM
SmartFit Plus (25mm S)	260mm	1300mm	150mm	2180mm	2.9 SQM
SmartFit Plus (45mm S & 45mm D)	260mm	1860mm	150mm	2180mm	4 SQM
Cord Loop & SmartRelease ™ Cord Loop	380mm	3000mm	250mm	3600mm	7.5 SQM
Cord Loop Top Down	610mm[3]				
Cord Loop Day & Night					
Corded	220mm	2500mm			5.5 SQM
Corded TDBU					
Corded Day & Night					
Patio Door Vertical	750mm	3700mm	600mm	3000mm	11.1 SQM
Patio Door Vertical Day & Night					

1. Maximum width is 1270mm for SmartFit™ Model A on 25mm single cell.
2. Maximum area is 2.6 SQM for SmartFit™ Model A on 25mm single cell.
3. Minimum width for height greater than 1828mm is 770mm.
4. Maximum height is 2200mm for 25mm single cell.
5. Minimum width for height greater than 2200mm is 570mm.
6. Minimum width for height greater than 2200mm is 800mm.

Disclaimer: Norman reserves all rights on updating or modification of any contents within this documentation without prior notification.

Max Frame to Frame Size for Decoflex™ (SmartFit™ with Frame) & Decoflex™ Day & Night (SmartFit™ Day & Night with Frame) & Decoflex™ for Skylights (SmartFit™ for Sloped Windows with Frame):

DecoFlex												
Frame Type	Frame Thickness (x2)	T - Post Thickness	Frame to Frame Width								Frame to Frame Height	
			No T-Post (1 Shade)		1 x T-Post (2 Shades)		2 x T-Post (3 Shades)		3 x T-Post (4 Shades)		Min. (mm)	Max. (mm)
			Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)		
L Frame / Hang Strip	22.2mm	25.4mm	270	1845	520	3675	770	5505	1020	7330	195	2240
Z Frame	22.2mm	25.4mm	270	1845	520	3675	770	5505	1020	7330	195	2240
50mm Deco Frame	50.8mm	25.4mm	330	1905	580	3730	830	5560	1080	7390	255	2300
76mm Deco Frame	76.2mm	25.4mm	380	1955	630	3780	880	5610	1130	7440	305	2350

DecoFlex Day & Night												
Frame Type	Frame Thickness (x2)	T - Post Thickness	Frame to Frame Width								Frame to Frame Height	
			No T-Post (1 Shade)		1 x T-Post (2 Shades)		2 x T-Post (3 Shades)		3 x T-Post (4 Shades)		Min. (mm)	Max. (mm)
			Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)		
L Frame / Hang Strip	22.2mm	25.4mm	270	1315	520	2615	770	3915	1020	5210	355	2240
Z Frame	22.2mm	25.4mm	270	1315	520	2615	770	3915	1020	5210	355	2240
50mm Deco Frame	50.8mm	25.4mm	330	1375	580	2670	830	3970	1080	5270	415	2300
76mm Deco Frame	76.2mm	25.4mm	380	1425	630	2720	880	4020	1130	5320	465	2350

DecoFlex For Skylights												
Frame Type	Frame Thickness (x2)	T - Post Thickness	Frame to Frame Width								Frame to Frame Height	
			No T-Post (1 Shade)		1 x T-Post (2 Shades)		2 x T-Post (3 Shades)		3 x T-Post (4 Shades)		Min. (mm)	Max. (mm)
			Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)		
L Frame	22.2mm	25.4mm	270	1545	520	3075	770	4605	1020	6130	195	3040
Z Frame	22.2mm	25.4mm	270	1545	520	3075	770	4605	1020	6130	195	3040

*The above is max frame to frame width, and each shade size must within the SmartFit™/SmartFit™ Day & Night / SmartFit™ for Sloped Windows size limitation.

Disclaimer: Norman reserves all rights on updating or modification of any contents within this documentation without prior notification.

Norman Australia Honeycomb Shade Program Binder				
Approver		**Custom Made Honeycomb Shade (Non-Motorisation)**	Code	P-HC-0126
			Edition	AX
Reviewer	Selina Chen		Page	19/71
Compiler	Orange Zeng		Date	15.07.2026

Single Shade for Breeze/Windsong/Ashton Fabric:

Lift Systems	Fabric	Width		Length		Max. Area
		Min	Max	Min	Max	
Woven Cordless	Breeze & Windsong & Ashton	400mm[1]	2100mm	260mm	2100mm	4.41 SQM
Woven Cordless TDBU		400mm[1]	1980mm	260mm	2100mm	4.16 SQM
Cord Loop & SmartRelease ™ Cord Loop	Windsong & Ashton	380mm	2100mm	260mm	2100mm	4.41 SQM
Cord Loop TD		610mm[2]	2100mm	260mm	2100mm	4.41 SQM
Cord Loop Day & Night		610mm[2]	2100mm	260mm	2100mm	4.41 SQM
SmartFit™	Windsong	220mm	1800mm	150mm	2200mm	4 SQM
SmartFit™ Day & Night		220mm	1800mm	310mm	2200mm	4 SQM
SmartFit™	Ashton	220mm	1270mm	150mm	2200mm	2.77 SQM
SmartFit™ Day & Night		220mm	1270mm	310mm	2200mm	2.77 SQM

1. For shades less than 485mm in width, the maximum height available is 1570mm.
2. For shades over 1828mm in height, the minimum width available is 770mm.
3. Ashton is not available in Cord Loop Day & Night.

Single Shade for Solus Fabric:

Lift Systems	Width		Height		Max. Area
	Min	Max	Min	Max	
SmartRise™ Cordless	400mm[2]	2500mm	250mm	2400mm	5.5 SQM
Cordless TDBU	400mm[3]				
Cordless Day & Night					
SmartFit™	220mm	1800mm	150mm	2200mm	4 SQM
SmartFit™ Day & Night	220mm	1800mm	310mm	2200mm	4 SQM
SmartFit Plus	260mm	1860mm	150mm	2180mm	4 SQM
Cord Loop & SmartRelease ™ Cord Loop	380mm	3000mm	250mm	3600mm	7.5 SQM
Cord Loop Top Down	610mm[1]				
Cord Loop Day & Night					
Corded	220mm	2500mm			5.5 SQM
Corded TDBU					
Corded Day & Night					

1. For shades over 1828mm in height, the minimum width available is 770mm.
2. Minimum width for height greater than 2200mm is 570mm.
3. Minimum width for height greater than 2200mm is 800mm.

Disclaimer: Norman reserves all rights on updating or modification of any contents within this documentation without prior notification.

Single Shade for Flame Resistant Fabrics:

Lift Systems	Width		Height		Max. Area
	Min	Max	Min	Max	
SmartRise™ Cordless	635mm	2500mm	250mm	2400mm[5]	5.5 SQM
Cordless TDBU	635mm[6]				
SmartFit™ Bottom Up	220mm	1820mm	150mm	2438mm	3.3 SQM
SmartFit™	220mm	1800mm[1]	150mm	2200mm	4 SQM[2]
SmartFit™ for Sloped Windows	220mm	1500mm	150mm	3000mm	4.5 SQM
SmartFit Plus (25mm S)	260mm	1300mm	150mm	2180mm	2.9 SQM
SmartFit Plus (45mm S)	260mm	1860mm	150mm	2180mm	4 SQM
Cord Loop & SmartRelease ™ Cord Loop	380mm	3000mm	250mm	3600mm	7.5 SQM
Cord Loop Top Down	610mm[3]				
Corded	220mm	2500mm			5.5 SQM
Corded TDBU					
Patio Door Vertical	750mm	3700mm	600mm	3000mm[4]	11.1 SQM

1. Maximum width is 1270mm for SmartFit™ Model A on 25mm single cell.
2. Maximum area is 2.6 SQM for SmartFit™ Model A on 25mm single cell.
3. For shades over 1828mm in height, the minimum width available is 770mm.
4. For 45mm Flame Resistant RD fabric the max. height for Patio Door Vertical is 2400mm.
5. Maximum height is 2200mm for 25mm single cell.
6. Minimum width for height greater than 2200mm is 800mm.

Disclaimer: Norman reserves all rights on updating or modification of any contents within this documentation without prior notification.